



DAXTEN POWER
beyond limits

®

SqA

AHU SERIES (SPECIAL MODEL)

THREE PHASE SERVO MOTOR CONTROL SYSTEM

AUTOMA

TIC VOLTAGE REGULATOR (AVR)

80KVA

APPLICATION



Data Center



Telecom



Quality



Server



Security



Medical



Network



Video



Banking



PC



FAX



Monitor



ADSL



Labs



Home Appliances



TECHNICAL SPECIFICATION

MODEL	AHU 80KVA
Input voltage range	380VAC ± 45% -25%
Output voltage	220VAC/380VAC ±2.5% Accuracy
PHASE	Three Phase +N+PE
Frequency	50Hz /60Hz
Response time	Within 0.3 sec. against 13% input voltage deviation
Power Factor	0.9
Ambient Temperature	-5°C ~ + 40°C
Ambient Humidity	Less than 90% (relative humidity)
Temperature Rise	Less than 75°C
Cooling System	Convection-cooled
Control System	DC servo-motor
Style	Stand-alone style
Insulation Resistance	More than 5 M ohm
Dielectric Strength	Tested at AC 1500V for 1 min
Equipped with	Over and Under Voltage and Phase Failure Device ,Manual Bypass 5 L.C.D Display With 3 L.E.D Lights

Product specification are subject to change without further notice